

## PHYSICAL PARAMETERS

Product Model	HW-MQSB-V2
Color	Black
Specification	720(length) *500 (width) *32 (arch height) mm
Weight	6.5kg
Connector	MC4
Warranty	25 years

## ELECTRICAL PERFORMANCE PARAMETERS

Chip type	copper, indium, gallium and selenium
Open-circuit voltage - Voc	10.6V
MaxPower - Pmax	32W (Standard Edition)
PMPP Current - Imp	3.6A
Short circuit current - Isc	4.0A
PMPP time voltage - Vmp	8.8V

## PERFORMANCE LEVEL

Load rating	5400pa
Waterproof grade	IP67
Fire rating	A
Hail resistance level	Level 4 (ANSI FM 4473)
Working temperature	-40°C~+85°C
Operating humidity	0~80%

The overall product warranty is 10 years, and the power guarantee by the 25th year, the power generation shall not be less than 85% of the nominal power

---

Beijing Shan Hu International Technology Co., Ltd

## PHYSICAL PARAMETERS

Product Model	HW-MQSB-V2
Color	Red
Specification	720(length) *500 (width) *32(arch height) mm
Weight	6.5kg
Connector	MC4
Warranty	25 years

## ELECTRICAL PERFORMANCE PARAMETERS

Chip type	copper, indium, gallium and selenium
Open-circuit voltage - Voc	10.5V
Maximum Power - Pmax	28W (Standard Edition)
PMPP Current - Imp	3.4A
Short circuit current - Isc	3.9A
PMPP time voltage - Vmp	8.4V

## PERFORMANCE LEVEL

Load rating	5400pa
Waterproof grade	IP67
Fire rating	A
Hail resistance level	Level 4 (ANSI FM 4473)
Working temperature	-40°C~+85°C
Operating humidity	0~80%

The overall product warranty is 10 years, and the power guarantee by the 25th year, the power generation shall not be less than 85% of the nominal power

---

Beijing Shan Hu International Technology Co., Ltd