



Description

- Suitable for PV system, equipped with a surge protector and an isolator, providing isolation, leakage and grounding protection.
- Enclosures are made of polycarbonate (PC-ABS) materials. IK08 high impact-resistance and light enough to easily carry. IP65 rating for outdoor installation, resisting UV radiation, water, dust, reducing corrosion.
- Through transparency cover, you can observe interior mechanism directly.
- Reliable components, with TUV, CE certificated, in accordance with IEC standard.
- IP65 cable connector. Waterproof cable connector & MC4 connector are optional.

Type of open door from right to left

Without Neutral Terminal Model

Model No.		Ways	Dimension(mm)		
PC	Code		L	W	H
LDDB4S6R	604342	6	165	200	108
LDDB4S9R	604343	9	219	200	108
LDDB4S12R	604344	12	273	215	118
LDDB4S18R	604345	18	381	215	118
LDDB4S24R	604346	24(2x12)	273	365	118
LDDB4S36R	604347	36(2x18)	381	365	118

With Neutral Terminal Model

Model No.		Ways	Dimension(mm)		
PC	Code		L	W	H
LDDB4S6RT	604312	6	165	200	108
LDDB4S9RT	604313	9	219	200	108
LDDB4S12RT	604314	12	273	215	118
LDDB4S18RT	604315	18	381	215	118
LDDB4S24RT	604316	24(2x12)	273	365	118
LDDB4S36RT	604317	36(2x18)	381	365	118